REGIONAL SERVICE & TRAINING CENTER

30 factory-certified technicians within the region

Stiles University is the industry's only nationally accredited workforce development program. Our team of certified professionals guide students through comprehensive, hands-on technical and application trainings designed to equip you with the knowledge you need to optimize your machinery and manufacturing practices.









HE | STILES

For more information contact your local salesperson, or email Annette Bilocca at: abilocca@stilesmachinery.com

Stiles Machinery Inc. 3965 44th St. SE Grand Rapids, MI 49512

616.698.7500 www.stilesmachinery.com

EDGETEQ S-500 SERIES

The HOMAG S-500 is the ultimate industrial strength edgebander in speed and automation. Bringing an industry leading machine in design, durability and performance, the S-500 delivers high-production capacity along with the latest technology in machine automation and controls. The S-500 is available in 2 coil or 6 coil magazine, left-hand and right-hand configurations, and airTec for zero edge processing.





S-500 SERIES | The HOMAG S-500 is the unrivaled heavy production edgebander in the industry equipped with a heavy-ridged frame, offering speeds up to 25 meters per minute with a small panel gap. The S-500 series is available in left-hand and right-hand configurations.





EDGETEQ S-512 Overview Video

_	•		•		
EDGE	T	EQ	s	-50	0
Over	vic	14/	۱/i	dar	

	EDGETEQ	EDGETEQ	EDGETEQ	EDGETEQ
EDGETEQ FEATURES	TAPE ROCKET	S-512 PUR/EVA	S-500 EVA	S-500 CLASSIC
Solid Strip Package				✓
Pre-Milling Unit	✓	✓	✓	✓
Pre-Melter	EVA	EVA/PUR Universal	EVA	EVA
Gluing Unit QA65	✓	✓	✓	✓
airTec		Optional	Optional	Optional
2-Coil	✓	✓	6-Coil Optional	6-Coil Optional
Snipping Unit	PK25	HL-81	PK25	PK25
Trimming Unit – Rough Trim			✓	✓
Trimming Unit – Fine Trim	2 Motors – 2 Profiles	Servo (2 Motors – 3 Profiles)		Servo (2 Motors – 3 Profiles)
Contour Trimming (Corner Rounding)		Servo (2 Motors – 3 Profiles)	Servo (4 Motors – 3 Profiles)	Servo (4 Motors – 3 Profiles)
Profile Scraper	Quick Change	Servo (2 Profiles)	Servo (7 Profiles)	Servo (7 Profiles)
Glue Joint Scraper (Flat Scrape)	✓	✓	✓	✓
Buffing Unit	✓	✓	✓	✓
Available in LH or RH Orientations	✓	✓	✓	✓
Sprayers Equipped	Separate / Detergent	Separate / Lubricant / Detergent	Separate / Detergent	Separate / Detergent
Feed Speed:	25 m/min (82ft/minute)	20 m/min (65ft/minute)	25 m/min (82ft/minute)	25 m/min (82ft/minute)
Contour Trimming Feed Speed:		20 m/min (65ft/minute)	25 m/min (82ft/minute)	25 m/min (82ft/minute)
Length:	7,365mm (24ft)	9,365mm (31ft)	8,865mm (29ft)	9,365mm (31ft)
Weight:	3,855kg (8,500lbs)	5,806kg (12,800lbs)	6,260kg (13,800lbs)	6,260kg (13,800lbs)























