

G330X

- Manual Copy Grinder
- Manual wheel forward/reverse adjustment
- Pneumatic wheel tilt adjustment
- Manual wheel grind angle adjustment
- Integrated coolant tank w/baffle and filter
- Integrated storage cabinet
- Adjustable arm rest
- Table mounted diamond dresser
- Table locks with micrometer
- Clean up hose with nozzle
- Quick change hubs
- 20W work lamp



Capacities

• Max length cutterhead:

Max cutting diameter:

Min cutting diameter:

• Max depth of profile:

Main motor

Coolant motor

Weight

320mm (12.59")

350mm (13.7")


70mm (2.75")

40mm (1.57")

2HP

1/4HP


650kgs (1433lbs)





Multi Styli Turret

- Fast adjustment to template
- Fast styli change
- Included styli
 - 4.7mm x 5pc
 - 4.0mm x 1pc
 - 3.0mm x 1pc
 - 2.0mm x 1pc





Rail & Bearing Carriage

- Supports heavy weight tooling, allowing them to move with ease
- Easy, smooth movement on chrome linear rails and ball bearings
- Integrated table clamps
- Integrated micrometer for straight tool grinding (no template)



Coolant Tank

Capacity Max/Min

- Integrated baffle
- Removable filter screen tray

36/18L

Grinding Wheel

Wheel diameter

Wheel bore

Wheel RPM

• Belt drive to wheel arbor

Analog clock for wheel lateral arbor adjustment

Carbide tool rest with integrated coolant nozzle


Quick change wheel hubs (3pcs)

ProLok wheel clamping

230mm


60mm

Variable 1500-3000RPM



Template Holder

- Full 12" inch clamping area
- Axial constant stops
- Analog clocks for precise template adjustment





Integrated machine storage for tools, wheel rack, and other accessories






G330XT

- Same features as G330X plus
- Powered wheel tilt adjustment
- Powered wheel angle adjustment
- Powered wheel advancement
- External coolant tank
- Pedestal operator control

Comfort Package

- G330XT Only
- Motorized grinding wheel angle adjust
- Motorized grinding wheel tilt adjust
- Motorized grinding wheel advance adjust



External Coolant Tank

- 120V secondary pump out motor
- Pump out hose with nozzle
- Caster wheels for easy movement
- Integrated filter tray
- Sight gauge
- Best use for switching between carbide and high-speed steel grinding. Suggest one tank for each type.



Pedestal Control

- G330XT Only
- Ergonomic eye level control panel
- Electronically variable wheel RPM control
- Electronic, hold to run, controls for:
 - Grinding wheel angle adjustment
 - Grinding wheel tilt +/- adjustment
 - Grinding wheel advancement adjustment



G650X

- Twin Grinding Centre
 - Dedicated Profile tool station
 - Dedicated Straight tool station
 - Fast station changeover with rotation. Automatic transfer of power and plumbing








G320A/B

Fully Automatic Grinding Center

- G320A is for straight knives only
- G320B is for straight knives and solid profile tool types



G320B

Shear tool cutting ability

Carriage can rotate to manage shear angled tools.

HSK tool hub adapter is optional



