PENTHO CONTROL





One machine for one or several different window types

The Pentho Control is produced with one or more long spindles and a noise reduced cut off saw. With the tool splitting technology tools from all the spindles can be combined with each other. The solid table can turn in two directions up to 45° to make angled windows. The Pentho Control can be entirely automated and be combined with a "Profil Control" in order to come to a complete window line.




The table can be swivelled 45° in two directions. The working surface of the table changes not in shape.



Each module is equipped with pneumatic aluminium protection plates.



Tools on the different 545 mm long spindles can be combined to make one profile.





7" touch panel for the full operation of the machine.





PENTHO CONTROL



TECHNICAL DETAILS

FRAME

Construction: Combined self supporting frame with a cage

construction

Safety screen: Pneumatic aluminium protection plates

Security: Conform CE.

TABLE

Table mounting: Horizontal on rails; extra solid

Movement: Manually; automatic movement option

Table: Swivelling +45° to -45°; fixed in height
Blowing system on table for cleaning

Backing wood: Round backing wood with 6 manual positions; clamp for

straight backing wood; pneumatic backing wood option

Clamps: 2 vertical pneumatic clamps

Length fence: 2.4 m with digital read-out and one large swivelling

back stop included

3.4 m and automatic length-fence option

Dimensions: 320 mm x 1000 mm (useable 160 mm x 1000 mm)

CUT OFF SAW

Motor: 2,2 kW - 3000 tpm

Adjustment: Hor. 150 mm -cut-off capacity 185 mm

Tool: Noise reduced saw included -diam. 450

Extraction: Ø 80 mm

Positioning: Manual; digital read-out or CNC option

VERTICAL SPINDLE (S)

Motor 7,5 kW; 11 kW option

RPM: 4000 tpm Suspension: Dove tail

Movement: Vertical 0 - 500 mm

Positioning: Vertical CNC-positioned with ball circulating screw

horizontal fix; on/off or CNC-positioned option

Spindle length: 545 mm with top bearing

Spindle Ø: Ø 50 mm

Tool Ø: Max. Ø 350 mm Extraction: Ø 180 mm

OPERATING SYSTEM

System: 7" touch panel standard

15" touch panel in separate control console for

extension to complete window line

STANDARD



Digital read-out and one large swiveling back stop



Pneumatic clams

OPTIONS



15" touch panel with separate control console



Automatic length-fence

