TWO HEAD SOLID WOOD SANDING MACHINE

# HEESEMANN JSM RC STANDARD 1100


The Heesemann JSM RC Standard two head wide belt sander delivers optimal calibration and solid wood finish sanding results. Ideal for solid wood calibration and finishing, the RC is loaded with features to make the job easy and the machine a pleasure to operate. This machine raises the bar on quality and features easy to use controls with controllable heads for quick and easy program changes, a combi head with acp air cushion pad technology, all controlled by an advanced touchscreen control. A robust lifting system with heavy duty jack screws ensure accuracy for years to come. The Heesemann JSM brings high performance sanding to a level previously not available.

| Specifications | |
|---|---|
| Sanding Heads | 2 |
| Sanding Width | 43” (1100 mm) |
| Working Thickness | 1/8” – 6.3” (3 mm – 160 mm) |
| Feed Speed | Variable / Inverter Driven |
| Controls | 15” Hi-Res Touch Screen |
| Head Type | 1: R Head - Steel Roller<br>2: C Head - Combi with acp |
| Pad System | ACP Air Cushion Pad System |
| Hold Down System | Hold Down Rollers |
| Machine Weight | ~ 5,000 lbs |
| Dust Extraction | ~ 2000 CFM |
| Full Load Amps | ~65A @ 480 V |



2 Heads with Air Cushion Pad




ACP ® Air Cushion Pad System

Poly-V drives & DC Motor Braking

15” High Resolution Control

## Advanced Features

- Profiled steel contact roller with grit compensation and automatic activation via control for ultimate performance
- Combi head with rubber contact roller and segmented pad for fine sanding versatility with automatic activation via control
- Helically grooved rollers with poly-v belt drives for maximum power and performance
- ACP air cushion pad technology for solid wood finish sanding with rise and fall control
- DC motor braking for maintenance free motor braking
- Contact free belt tracking for worry free operation
- 15” High Resolution Touchscreen for intuitive operation
- Moving passline with 4 heavy duty dual supported jack screw lifting system
- Thick conveyor belt with automatic conveyor belt tracking