


IRONWOOD SL300 SLIDING TABLE SAW



IRONWOOD's SL Series of sliding table saws bring ultimate versatility and flexibility to an operator friendly cutting solution. Fused to be a blend of innovation, dependability and quality, the SL series delivers the quality and precision required for the final chip-free cut, improving the results of subsequent machining.

ADVANCED FEATURES

| Technical Specifications | SL300 |
|--------------------------|------------------------------|
| Tilting of arbor | 0-45.5° |
| Cutting length | 122" (3110 mm) |
| Rip Capacity | 51" (1300mm) |
| Cutting depth max - 90° | 4.8" (125 mm) |
| Cutting depth max - 45° | 3.34" (85 mm) |
| Main saw motor | 7.5 HP (5.5 kW) IE3 |
| Saw speed | 3000/4000/5000 RPM |
| Standard main blade | 305mm x 3.2mm x 30mm |
| Main blade arbor | 30mm wth 2 pin holes |
| Max Blade Size | 16" (400 mm) |
| Scoring saw motor | 1 HP (0.75 kW) 8000 RPM |
| Scoring blade diameter | 120mm |
| Dust extraction | 800CFM - (2) 3.9" Ø (100 mm) |
| Electrical requirement | 230V or 460V 3-Phase 60 |
| Amperage | 230V: 14.75A 460V: 8.5A |
| Machine weight | 2,921 lbs. (1,325 kg) |

- 3200mm (10') Sliding Table
- Overhead controller with keypad entry for all dimensions
- Motorized rise, fall, and tilt via controller adjustment
- Motorized rip fence
- Automatic blade compensation adjusts axes to maintain parameters when blade is tilted.
- Crosscut Miter Fence with two flips stops and max distance of 3200mm with angle capacity from 0 - 49° and optional digital readout
- Motorized 2-axis scoring unit with quick adjust Leitz unit
- Aircraft grade aluminum sliding table
- Perfected, vertical guidance for accurate, square cuts over the full cutting length
- ProLock System for quick and easy blade changes
- Overhead Blade Guard for increased operator safety

IRONWOOD



**Panel/Wood
MACHINERY**
MACHINES SOLUTIONS SYSTEMS

STILES | HC
A HOMAG COMPANY